

## 'PERFORMANCE DATA' PRODUCTS LISTING (PDPL)

<u>ID # [X-File #]</u>	<u>Product Trade Name / Manufacturer</u>	<u>Product Description and Manufacturer Suggested Use</u>	<u>Vendor Certifies Compliance With:</u>	<u>Rev. Date</u>
<u>CATEGORY</u>	<u>Contact Reference</u>			
<b>A.1 Anchoring Epoxies</b>				
98-020	<b>CCS Grout, Dowel/Rebar/Bolt ChemCo Systems, Inc.</b> John Bors @ 650 802 1095, CA (California) <u>Local Rep.:</u> None	<i>Product is a two component, high modulus and creep resistance epoxy paste adhesive designed specifically for grouting dowels, bolts and rebar in hardened concrete, masonry and stone at low or moderate ambient temperatures when a short working life/cure is desired.</i>	ASTM C 881, Type IV, Grade 1	10/00
92-168	<b>CIA-Gel Epoxy Covert Operations, Inc.</b> @ 562 986 4212, CA (California) <u>Local Rep.:</u> Alternative Supply 801 576 1671	<i>Product is a structural epoxy resin. It is used to anchor threaded rod and reinforcing dowels to hardened concrete and masonry.</i>	ASTM C 881, Type I, III & IV, Grade 3, Class B, C, D, E, & F	10/00
02-039	<b>Rescon Gel Anchor LV, FS Dayton Superior Chemical Corp.</b> Darryl Anderson @ 303 286 9071, CO (Colorado) <u>Local Rep.:</u> Forshor 801 487 1656	<i>Product is a fast set pumpable two component 100% solids, high modulus, moisture tolerant epoxy gel adhesive for anchoring dowels, bolts and reinforcing steel.</i>	ASTM C 881, Type II, Grade 3, Class B & C.	8/02
02-041	<b>Rescon Gel Anchor FS Dayton Superior Chemical Corp.</b> Darryl Anderson @ 303 286 9071, CO (Colorado) <u>Local Rep.:</u> Forshor 801 487 1656	<i>Product is a fast set, two component, 100% solids, high modulus, epoxy gel adhesive for anchoring bolts, dowels and reinforcing steel in concrete.</i>	ASTM C 881, Type I, II, IV and V, Grade 3, Class B & C.	8/02

<u>ID # [X-File #]</u>	<u>Product Trade Name / Manufacturer</u> <u>CATEGORY</u>	<u>Contact Reference</u>	<u>Product Description and</u> <u>Manufacturer Suggested Use</u>	<u>Vendor Certifies</u> <u>Compliance With:</u>	<u>Rev.</u> <u>Date</u>
<b>A.1 Anchoring Epoxies</b>					
02-042	<b>Rescon Gel Anchor</b> <b>Dayton Superior Chemical Corp.</b> Darryl Anderson @ 303 286 9071, CO (Colorado) <u>Local Rep.:</u> Forshor 801 487 1656		<i>Product is a two component, 100% solids, high modulus, epoxy gel adhesive that is moisture tolerant for anchoring bolts, dowels and reinforcing steel in concrete.</i>	ASTM C 881, Type I, II, IV and V, Grade 3, Class B & C	8/02
95-112	<b>Resi-Bond (J-58)</b> <b>Dayton Superior Chemical Corp.</b> Art Weiss @ 800 745 3708, IL (Illinois) <u>Local Rep.:</u> Dayton Superior (Pat Fordham) 801 942 0057		<i>Product is a 100% solids, high modulus, high strength epoxy bonding adhesive. Bonds fresh concrete to hardened concrete and steel to fresh or hardened concrete.</i>	ASTM C 881, Type I & II, Grade 2, Class B & C	10/00
95-114	<b>Sure-Anchor Epoxy (J-50)</b> <b>Dayton Superior Chemical Corp.</b> Art Weiss @ 800 745 3708, IL (Illinois) <u>Local Rep.:</u> Dayton Superior (Pat Fordham) 801 942 0057		<i>Product is a 100% solids, high-modulus, high strength, epoxy gel adhesive for anchoring bolts, dowels and reinforcing steel into concrete.</i>	ASTM C 881, Type I & II, Grade 3 Class B & C	10/00
99-148	<b>Sure Anchor I (J-51)</b> <b>Dayton Superior Chemical Corp.</b> Jerome Ford @ 800 745 3707, IL (Illinois) <u>Local Rep.:</u> Intermountain Concrete Specialty 801 486 5311		<i>Product is 100% solids, high modulus and strength epoxy gel adhesive. Designed to anchor bolts, dowels and reinforcing steel into concrete.</i>	ASTM C 881, Type I, II, IV & V, Grade 3, Class B & C, except for gel time	10/00
99-060	<b>Five Star RS Anchor Gel</b> <b>Five Star Products, Inc.</b> Chris Piekos @ 203 336 7900, CT (Connecticut) <u>Local Rep.:</u> Gene Silvey/Five Star 360 225 6468		<i>Product is a rapid setting, two component, 100% solids structural epoxy for anchoring rods, bars and bolts in concrete.</i>	ASTM C 881, Type I & IV, Class B & C, Grade 3	10/00

<u>ID # [X-File #]</u>	<u>Product Trade Name / Manufacturer</u>	<u>Product Description and Manufacturer Suggested Use</u>	<u>Vendor Certifies Compliance With:</u>	<u>Rev. Date</u>
<u>CATEGORY</u>	<u>Contact Reference</u>			
<b>A.1 Anchoring Epoxies</b>				
01-061	<b>HIT RE 500</b> <b>Hilti, Inc.</b> Christian Fogstad @ 970 494 1666, CO (Colorado) <u>Local Rep.:</u> Jim Carpenter 801 209 7004	<i>Product is a two part anchoring epoxy to anchor threaded bars and rebar to concrete.</i>	ASTM C 881, Type IV, Grade 3, Class A, B, C except gel time	10/01
99-092	<b>HSE-2421 High Strength Epoxy</b> <b>Hilti, Inc.</b> William Gould @ 719 282 8719, CO (Colorado) <u>Local Rep.:</u> Hilti, Inc 801 487 1502	<i>Product is a high strength anchoring epoxy for concrete and doweling operations. It replaces Hilti's HSE 2+1.</i>	ASTM C 881, Type IV, Grade 3, Class A, B, C except gel time	10/00
96-082	<b>EPCON Granite 5 Epoxy</b> <b>ITW Ramset/Red Head</b> Christopher La Vine @ 630 350 0370, IL (Illinois) <u>Local Rep.:</u> same as above	<i>Product is a granite filled, slow cure, epoxy injection system. Designed for high strength, low deflection anchor or dowel rod installation in solid concrete or masonry construction fastening applications.</i>	ASTM C 881, Type II, Grade 3	10/00
98-017	<b>EPCON Ceramic 6 Epoxy</b> <b>ITW Ramset/Red Head</b> Amy Kolczak @ 630 350 0570, IL (Illinois) <u>Local Rep.:</u> Intermountain Fastening Systems 801 466 0307	<i>Product is a ceramic-filled epoxy used for anchoring threaded rod, rebar and dowel rod into solid concrete and hollow block.</i>	ASTM C 881, Type IV, Grade 3	10/00
98-085	<b>Concresive 1420</b> <b>Master Builders, Inc.</b> Chris Ball @ 216 831 5500, OH (Ohio) <u>Local Rep.:</u> Conesco 801 972 8777	<i>Product is a 100% solids, two component general purpose epoxy adhesive, designed for anchoring of fasteners, rebar and dowels into concrete.</i>	ASTM C 881 Type I, Grade 3, Class B	10/00

<u>ID # [X-File #]</u>	<u>Product Trade Name / Manufacturer</u> <u>CATEGORY</u>	<u>Contact Reference</u>	<u>Product Description and</u> <u>Manufacturer Suggested Use</u>	<u>Vendor Certifies</u> <u>Compliance With:</u>	<u>Rev.</u> <u>Date</u>
<b>A.1 Anchoring Epoxies</b>					
92-105	<b>Power Fast Epoxy aka Foil-Fast Inj.</b> <b>Powers Rawl Company</b> Clyde Burnett @ 914 235 6300, NY (New York) <u>Local Rep.:</u> Rawl Plug-Salt Lake		<i>A two-part structural epoxy anchoring system for use in concrete. Available in foil packs for better dispensing methods and ease of disposal.</i>	ASTM C 881, Type I, II, IV & V	10/00
02-045	<b>Sikadur Anchor Fix-3FS</b> <b>Sika Chemical Corporation</b> Scott Isaac @ 800 933 7452, NJ (New Jersey) <u>Local Rep.:</u> Intermountain Concrete/Smalley & Co. 801 486 5311		<i>Product is a 100% solids, moisture tolerant, high modulus, high strength structural epoxy.</i>	ASTM C 881, Type I, II, IV and V.	8/02
02-046	<b>Sikadur Anchor Fix 4</b> <b>Sika Chemical Corporation</b> Scott Isaac @ 801 282 5440, NJ (New Jersey) <u>Local Rep.:</u> Intermountain Concrete/Smalley & Co. 801 486 5311		<i>Product is a two component, solvent free, moisture tolerant, high modulus, high strength structural epoxy.</i>	ASTM C 881, Type I, II, IV and V.	8/02
92-149	<b>Sikadur Injection Gel</b> <b>Sika Chemical Corporation</b> Scott Isaac @ 801 282 5440, UT (Utah) <u>Local Rep.:</u> Intermountain Concrete/Smalley & Co. 801 486 5311		<i>Non-abrasive epoxy used for grouting and crack repair. May be used on structural crack repairs NOT exceeding 1/4" width. Available in no-mix, 13-fl oz disposable cartridges.</i>	ASTM C 881, Type I, Grade 3, Class B, C.	9/01
99-023	<b>Sikadur DOT-SP13</b> <b>Sika Chemical Corporation</b> Mark Tharnish/ Scott Isaac @ 801 282 5440, UT (Utah) <u>Local Rep.:</u> Intermountain Concrete/Smalley & Co. 801 486 5311		<i>Product is a two component, 100% solids, high strength structural epoxy. Formulated for grouting/anchoring of dowel bars in concrete.</i>	ASTM C 881	10/00

<u>ID # [X-File #]</u>	<u>Product Trade Name / Manufacturer</u> <u>CATEGORY</u>	<u>Contact Reference</u>	<u>Product Description and</u> <u>Manufacturer Suggested Use</u>	<u>Vendor Certifies</u> <u>Compliance With:</u>	<u>Rev.</u> <u>Date</u>
<b>A.1 Anchoring Epoxies</b>					
00-090	<b>Set High Strength Epoxy</b> <b>Simpson Strong-Tie Co.</b> Russ Silver @ 800 999 5099, CA (California) <u>Local Rep.:</u> Action Bolt & Stud Welding 916 416 7688		<i>Product is a two component, 100% solids high strength epoxy anchoring system.</i>	ASTM C 881, Type I, II, IV & V, Grade 3, Class B, C & D	10/00
00-091	<b>Epoxy-Tie ET</b> <b>Simpson Strong-Tie Co.</b> Russell Silver @ 800 999 5099, CA (California) <u>Local Rep.:</u> White Cap Industries 916 416 7688		<i>Product is a two component anchoring epoxy based system for use as a high strength, non-shrink anchor grouting material.</i>	ASTM C 881 Type I, II, IV & V, Grade 3, Class B & C	10/00
00-080	<b>Dural Fast Set Epoxy LV</b> <b>Tamms Industries</b> Kristin Carlson @ 800 218 2667, OH (Ohio) <u>Local Rep.:</u> For-Shor, Steve Bright(801 487 1656) 303 487 1977		<i>Product is a two part 100 % solids moisture insensitive high strength, fast setting epoxy resin. Designed as an anchor bolt grout for vertical holes.</i>	ASTM C 881, Type I, Class A & B, Grade 1	10/00
97-173	<b>Ultrabond 1300</b> <b>U.S. Anchor Corporation</b> @ 305 882 8200, FL (Florida) <u>Local Rep.:</u> Utah Fasteners 801 466 6116		<i>Product is a two component, 100% solids, ceramic blend epoxy. Recommended for anchoring and doweling in vertical, horizontal and overhead applications.</i>	ASTM C 881	10/00
97-175	<b>Ultrabond 3</b> <b>U.S. Anchor Corporation</b> @ 800 872 3330, FL (Florida) <u>Local Rep.:</u> Utah Fasteners 801 466 6116		<i>Product is a high strength, ceramic blend epoxy that is hi-mod for anchoring or repairing concrete. Ultrafast cure formula designed for cold weather applications.</i>	ASTM C 881	10/00

<u>ID # [X-File #]</u>	<u>Product Trade Name / Manufacturer</u>	<u>Product Description and Manufacturer Suggested Use</u>	<u>Vendor Certifies Compliance With:</u>	<u>Rev. Date</u>
<u>CATEGORY</u>	<u>Contact Reference</u>			
<b>A.1 Anchoring Epoxies</b>				
97-253	<b>Anchor-It HST-200</b> <b>US Anchor Corporation</b> David Iwata @ 800 262 4748, WA (Washington) <u>Local Rep.:</u> Utah Fasteners 801 466 6116	<i>Product is a two component, 100% solids epoxy paste adhesive designed for anchor grouting. High temp/extended set formula (45F to 120F application range)</i>	ASTM C 881, Type I, IV & V, Grade 3, Class B & C	10/00
97-254	<b>Anchor-It HS 200</b> <b>US Anchor Corporation</b> David Iwata @ 800 262 4748, WA (Washington) <u>Local Rep.:</u> Utah Fasteners 801 466 6116	<i>Product is a two component, 100% solids epoxy paste adhesive designed for anchor grouting. Moderate temp/extended set formula (35F to 110F application range)</i>	ASTM C 881, Type I, IV & V, Grade 3, Class A, B & C	10/00
01-026	<b>Pro-Poxy 300</b> <b>Unitex</b> Jerry Byrne @ 816 7700, MO (Missouri) <u>Local Rep.:</u> Intermountain Concrete Specialties 801 486 5311	<i>Product is a solvent free, moisture insensitive, two component structural epoxy adhesive. Recommended for grouting bolts, pins and dowels (vertical or overhead)</i>	ASTM C 881-90, Types I & IV, Grade 3, Classes B & C	3/02